



RP10 - P

Ralla su perni
Fifth wheel with pivot bearings
Sattelkupplung mit Bolzenlagerung
Sellette d'attelage avec articulation à boulons
Упорные подшипники на пальцах

| | | |
|------------|---|---------------------|
| 2'' | Omologazione - Homologation Genehmigung - Homologation Сертификация | 94 / 20 / CE |
| | | |

Dati tecnici - Technical data - Technische Daten - Données techniques - Технические данные

| Codice Article number Artikelnummer Code article Код | Altezza H H-Height H-Bauhöhe Hauteur H Высота H mm | Valore D D-Value D-Wert Valeur D Величина D kN | Carico verticale U Vertical load U Sattellast U Charge vertical U Вертикальный груз U Ton | Peso Weight Gewicht Poids Вес kg | 94 / 20 / CE | |
|--|---|---|--|---|--|---|
| | | | | | Classe Class Klasse Classe Класс | Omologazione Homologation Genehmigung Homologation Сертификация |
| F2P1 B 10 | 140 | 152 | 20 | 139 | G50-X | e11/00-4649 |
| F2P1 B 20 | 150 | 152 | 20 | 141 | G50-X | e11/00-4649 |
| F2P1 B 30 | 185 | 152 | 20 | 143 | G50-X | e11/00-4649 |
| F2P1 B 40 | 225 | 152 | 20 | 148 | G50-X | e11/00-4649 |
| F2P1 G 10 | 140 | 152 | 20 | 139 | G50-X | e11/00-4649 |
| F2P1 G 20 | 150 | 152 | 20 | 141 | G50-X | e11/00-4649 |
| F2P1 G 30 | 185 | 152 | 20 | 143 | G50-X | e11/00-4649 |
| F2P1 G 40 | 225 | 152 | 20 | 150 | G50-X | e11/00-4649 |

B = Piatto autolubrificante / Autolube plate / Wartungsarme Ausführung mit Gleitscheiben / Patins auto-lubrifiants / Самосмазывающаяся плита

G = Piatto standard / Standard greasing plate / Ausführung mit Zentralschmieranschluß / Plaque à graisser / Упорные подшипники со стандартной смазкой

